



SCALE 1:40



**KENGURU
PRO**

"KENGURU PRO" LTD

Address: Lauteres street 4, Riga, Latvia, LV-1002
 VAT Reg. No. 40103750152
 Bank: A/S Luminor bank, SWIFT: RIKOLV2X,
 Bank Account: LV65RIKO0002930161161
 e-mail: info@kengurupro.eu
 www.kengurupro.eu

K-013

KENGURU Standard



The complex consists of ten vertical columns of different height, three crossbars 490 mm in length, three crossbars 1200 mm in length, parallel bars that consist of two horizontal crossbars, with the length of the bars – 1758 mm, Swedish wall and aluminium bench for abs. Optionally, two 1200 mm crossbars can be re-designed to be 1758 mm in length. Height of the Swedish wall – 2073 mm. The distance between the crossbars of the Swedish wall – 407 mm. Construction is secured together with siluminium clamps. Weight- 129,5 kg.

Installation instructions:

- Choose a suitable underground for the unit (see page 2, table 2)!
- Prepare the construction pit with a drilling machine or other devices.
- Before pouring the concrete all structures elements must be leveled and fixed.
- Complex elements must be fixed and bolted together with metal clamps.
- Ready-made C25 concrete should be used.
- Crossbars installation height can be changed according to customer's wishes.
- Approximately 0,15m³ concrete is needed for each spot foundation.
- Under the structures we recommend to install absorbing rubber cover.

The size of the hole for the foundation is depending on the consistency of the ground. The dimensions mentioned above are applicable for normal conditions with firm ground. If the ground is extremely soft, a much bigger foundation is needed. Use only appropriate material and follow the installation instructions closely!!!

Foundation plan and area of movement of the K-013 KENGURU Standard

Foundation plan and area of movement of the K-013 KENGURU Standard				Technical information	
Foundation when using Shock absorbing underground (synthetic - rubber granulates)		Beveling of foundation when using loose filling material		width:	2612 mm
				height:	2650 mm
				length:	3282 mm
				largest part:	3350 mm
				weight:	129,5 kg
				floor space required:	6932 x 5716 mm
				pipe measurements:	diameter: wall thickness:
				108 mm	3.0 mm
				42.4 mm	3.0 mm
				33.7 mm	3.0 mm
				columns Ø108mm:	anodized profilled aluminium tube AW6060 (Silver color)
				elements:	stainless steel AISI 304, brushed surface
				metal clamps:	siluminium, powder coated, RAL 9005 (pure black)
				bolts for metal clamps:	stainless steel, Pin Hex Button Head Security bolts M10
				bench beam measurements:	Height, width (mm) Length (mm)
					100x100 1500
				aluminium beams:	silver color, anodized AW 6060, 2.0 mm
				max. free fall height:	< 2450 mm possible underground see DIN 79000:2012-05 Tab.2 or installation instructions
				user height:	> 140 cm
				maximum user weight:	130 kg
				certificates:	TÜV Rheinland InterCert Kft.

