



SCALE 1:40



LTD "KENGURU PRO"  
 Address: Lauteres street 4, Riga, Latvia, LV-1002  
 VAT Reg. No. 40103750152  
 Bank: LUMINOR A/S , SWIFT: RIKOLV2X ,  
 Bank Account: LV65RIKO0002930161161  
 e-mail: info@kengurupro.eu  
 www.kengurupro.eu

K-008\_kids

Low parallel bars



The complex consists of two curved low parallel bars. Length of the bars 1240mm, height- 700mm, distance between the bars- 400mm.

**Installation instructions:**

- Choose a suitable underground for the unit **according EN1176-1 annex I table I.1**
- Prepare the construction pit with a drilling machine or other devices.
- Before pouring the concrete all structures elements must be leveled and fixed.
- Complex elements must be fixed and bolted together with metal clamps.
- Ready-made C25 concrete should be used.
- Crossbars installation height can be changed according to customer's wishes.
- Approximately 0,15m<sup>3</sup> concrete is needed for each spot foundation.
- Under the structures we recommend to install absorbing rubber cover.

The size of the hole for the foundation is depending on the consistency of the ground. The dimensions mentioned above are applicable for normal conditions with firm ground. If the ground is extremely soft, a much bigger foundation is needed. Use only appropriate material and follow the installation instructions closely!!!

Foundation plan and area of movement				Technical information	
Foundation when using Shock absorbing underground (synthetic – rubber granulates)		Beveling of foundation when using loose filling material		width:	448 mm
				height:	700 mm
				length:	1240 mm
				largest part:	1340 mm
				weight:	40 kg
				floor space required:	3448 x 4240 mm
				pipe measurements:	diameter: wall thickness:
					48 mm 3.2 mm
				metal parts:	steel, galvanized, powder coated RAL 7016 (anthracite grey)
				max. free fall height:	< 700 mm
				user age:	3-14 years
				certificates:	TÜV Rheinland InterCert Kft.

